

NDT Sweeper™

Manual 2D Encoded Ultrasonic Scanner



Eddyfi Technologies

Delivering the Zetec Inspection Advantage

STAY AHEAD OF THE CURVE OR FLAT SURFACES

NDT Sweeper™ is a highly versatile manual 2D encoded scanner that is the perfect tool for quick Ultrasonic Testing (UT) examinations.

NDT Sweeper can virtually replace multiple specialized scanners due to its ability to scan both flat and curved surfaces. It's ideal for various applications including long seam weld inspections and corrosion mapping.

Thanks to its small, lightweight, and ergonomic design, NDT Sweeper can easily scan in many difficult-to-reach areas eliminating the need to deploy an automatic scanner in those situations. Unlike wheel probes, both axes are encoded so there is no need to draw an index line on the specimen when scanning.



Innovative design

- Two integrated encoders; 2D scanning precision.
- Non-marring wheels with integrated magnets; safe to use on composite, easy to use on steel.
- Brake that locks the the scanner at the desired position.
- Individual probe suspension that can be fixed axially or laterally.
- Can support up to two Phased Array (PA) probes at the same time; compatible with most PA wedges.

Highly versatile tool

- Perfectly suited for long seam weld inspection on flat specimen or pipe, and for corrosion mapping.
- Easy to deploy and able to encode in raster scan across long distances, providing C-scan mapping of large composite parts.
- Quick and efficient solution for the assessment of damaged or freshly repaired carbon-fiber-reinforced polymer, or CFRP, surfaces.



SPECIFICATIONS

INSTRUMENT

Dimensions (h x l x w)	70 x 144 x 146 mm (2.75 x 5.67 x 5.75 in) without probe
Weight	1.2 kg (2.7 lb)
Pipe Range, Circumferential	100 mm (4 in) NPS (115 mm/4.5 in) to flat
Pipe Range, Longitudinal	100 mm (4 in) NPS (115 mm/4.5 in) to flat
Radial Clearance	48 mm (1.9 in) on a 100 mm (4 in) NPS pipe; 70 mm (2.8 in) on plane surface
Probe Holding Capacity	2 phased array probes with option
PA Probe Holder Minimum Wedge Width	15.6 mm (0.61 in)
PA Probe Holder Maximum Wedge Width	75.6 mm (2.98 in)
Umbilical Length	3 m (10 ft)
Operating Temperature	-20°C (-4°F) to 50°C (122°F)
Environmental Sealing	Submersible



The information in this document is accurate as of its publication. Actual products may differ from those presented herein. © 2022 Eddyfi Canada, Inc. Eddyfi Technologies, Eddyfi, Zetec, Sweeper, TOPAZ, UltraVision and their associated logos are trademarks or registered trademarks of Eddyfi Technologies (wholly owned subsidiary of Eddyfi Canada, Inc.) in Canada and/or other countries. Eddyfi Technologies reserves the right to change product offerings and specifications without notice.

www.eddyfi.com

sales@eddyfi.com



Eddyfi Technologies

Delivering the Zetec Inspection Advantage